

FINISHED WALL

RISER CLEANOUT TEE WITH BRONZE PLUG, JR SMITH #4531Y OR APPROVED EQUAL

WHEN A BACKWATER VALVE IS INSTALLED DOWNSTREAM OF CLEANOUT, ENGRAVE "BACKWATER VALVE DOWNSTREAM" ON PLUG

INTERIOR-POLISHED STAINLESS STEEL COVER EXTERIOR-PRIME COATED STEEL COVER 24 GA. MINIMUM

-CUT CABINET BACK AND INSTALL COVER AT BACK OF CABINET. WHEN CABINET IS LOCATED AT A FIRE RATED WALL, INSTALL COVER ON WALL AND CUT OPENING IN CABINET TO ALLOW FOR REMOVAL OF COVER

CABINET BACK, WHERE OCCURS

- WASTE PIPE SIZE PER PLANS

FINISHED FLOOR

CLEANOUTS IN PIPING 2" OR LESS SHALL HAVE A CLEARANCE OF NOT LESS THAN 12" IN FRONT OF THE CLEANOUT, CLEANOUTS IN PIPING LARGER THAN 2" INCHES SHALL HAVE A CLEARANCE OF NOT LESS THAN 18".

CLEANOUTS:	CPC TABLE 707.1
PIPE SIZE	CLEANOUT SIZE
1½"-2"	1½"
2½"-3"	2½"
4"& LARGER	3½"

STANDARD CURRENT AS OF: 01/01/2025 APPROVED BY: NOTES:

