

2008

BEST PRACTICES



UC/CSU/CCC Sustainability Conference Cal Poly San Luis Obispo, 2008

The **Best Practice Awards Program** is created by the UC/CSU/IOU Energy Efficiency Partnership Program and funded under the auspices of the California Public Utilities Commission



AIA CONTINUING EDUCATION

The UC Project Management Institute is a Registered Provider with The American Institute of Architects Continuing Education Systems. Credit earned on completion of this program will be reported to CES Records for AIA members. Certificates of Completion for non-AIA members are available upon request (emily.montan@ucop.edu).

This program is registered with the AIA-CES for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product. Questions related to specific materials, methods and services will be addressed at the conclusion of this presentation.



ENGINEERING IV SATELLITE CHILLER PLANT

- Cal Poly San Luis Obispo
- Category: HVAC Design, New Construction
- Presented by Dennis K. Elliot, PE, CEM
Manager of Engineering and Utilities



CAMPUS CENTRAL PLANT

- Central Chiller Plant built in 1997 as part of \$26M Utilidor Project
- Original capacity 600 tons
- Designed for future TES
- Expanded to 1200 tons in 2003 by relocation of two 300 ton chillers from the Performing Arts Center
- CHW distribution only serves South half of campus
- Life cycle cost analysis showed cooling via central plant CHW cost approximately 50% less than local cooling equipment



TYPICAL AIR CONDITIONING APPROACH

- Typical solution for buildings not served by central plant:
 - Cooling system sized for peak building load – little use of diversity
 - Air cooled chillers for large building wide loads
 - Package/split DX units for small/concentrated/critical loads
 - Efficiencies can range from 0.8 - 1.2 kW/ton
 - Compliant with Title 24, but much room for improvement




DESIRED AIR CONDITIONING APPROACH

- Use water cooled chillers for building wide loads – central plant is best
- Larger chillers = higher efficiency, lower maintenance - efficiencies can range from 0.4-0.6 kW/ton – 50% better than air cooled
- Central plant provides redundancy and allows for load diversity
- Use chilled water fan coils for concentrated/critical loads if campus has 24 hour CHW
- Use high efficiency DX cooling if 24 hour CHW is not available from central plant
- Title 24 allows DX equipment with SEER of 10-13. Units available with SEER of 19-23.
- Specify minimum efficiency in campus standards!



CAMPUS GROWTH AND MASTER PLANNING

- Most new construction requiring air conditioning
 - Increased equipment loads
 - Changing expectations
- Facilities trying to stem the proliferation of package AC units
- Campus committed to using central plant CHW whenever possible
- Next big wave of construction would be in the N/W quadrant of campus – Eng III, Eng IV, and Bonderson
- CHW distribution not available to site
- Project budgets could not afford Central Plant/Utilidor upgrades



NEW ENGINEERING QUAD

- Engineering III
 - Completed 2002
 - 40,000 gsf
- Bonderson Projects Building
 - Completed 2006
 - 19,000 gsf
- Engineering IV
 - Completed 2007
 - 105,000 gsf



DESIGN FOR ENG III, ENG IV, BONDERSON

- These capital projects could not afford a multimillion dollar upgrade to the central plant and distribution
- Local cooling would be necessary until the next major plant expansion could take place
- Campus was committed to future integration with the central plant
- Settled on a satellite chiller plant, using water cooled chillers, that would serve all three buildings
- CHW lines stubbed out in the street for future connection to Utilidor



ENGINEERING IV CHILLER PLANT

- Eng III built for future chilled water – DX used only for critical loads
- Satellite chiller plant built as part of Eng IV project to serve all 3 bldgs
- Equipment located centrally
- Selected two Carrier 210 ton 30HXC206 “Evergreen” water cooled screw chillers – provides redundancy and unloading capability
- Chillers rated at 0.53 kW/ton
- Good turn down ratio for part load conditions
- Uses R134A refrigerant – zero ozone depletion potential (ODP) and modest global warming potential (GWP)




ENGINEERING IV CHILLER PLANT

- Project Results:
 - Chiller Plant cost - \$450K
 - Capital cost was \$50K LESS than local air cooled chillers in each building
 - Load diversity allowed for smaller total equipment size
 - Two chillers provides redundancy not feasible for each of 3 bldgs
 - Some increased cost for extended piping and electrical service, offset by having fewer pieces of major equipment and smaller total size
 - Annual energy savings of 150,000 kWh and \$15,000 per year



FUTURE PLANT / UTILIDOR / TES UPGRADE

- 1200 ton chiller plant approaching capacity, not adequate to serve new Center for Science building in 2011
- Performed utility master plan/feasibility study to determine utility growth needs and priorities (CHW was first!)
- Obtained \$10M funding as part of Center for Science project for CHW plant and utilidor upgrade
- Will install new 1350 ton centrifugal variable speed chiller – phase I of an eventual 5,000 ton build-out
- Complete CHW piping in Utilidor
- Install 19,000 ton-hour TES tank
- Connect Satellite Plant to Utilidor – can run in 3 different modes – central plant/local chiller/hybrid



OTHER TES IDEAS...



BEST PRACTICES

2008



OTHER TES IDEAS...



BEST PRACTICES

2008



OTHER TES IDEAS...



BEST PRACTICES

2008



LESSONS LEARNED

- Have a utility master plan and update it as your campus master plan/capital improvement plan changes
- Develop campus standards that include utility systems, energy management, metering, campus preferred equipment, design guidelines, and minimum energy efficiency criteria – set high goals and challenge your consultants to meet them
- Cooling from a water cooled central plant is approximately 50% cheaper than local air cooled equipment from a life cycle cost standpoint
- Be careful when evaluating variable speed chillers – if chillers will usually run fully loaded, there is no benefit. If you will usually run at part load or have TES, a significant efficiency increase is possible
- Address sound attenuation in chiller designs



SPECIAL THANKS TO:

- Goss Engineering – Utilidor Project and Utility Master Plans
- Salas & O'Brien Engineers – Chiller Plant/Utilidor Upgrade/TES
- AC Martin Partners – Architect for Engineering IV
- Innovative Engineering Group – Mech Engineer for Engineering IV
- Bob Kitamura and Joel Neel – Facilities Planning



CONTACT INFO AND WEB LINKS

- For info, contact Dennis Elliot, Mgr of Engineering and Utilities
(805) 756-2090, delliot@calpoly.edu
- Facilities Sustainability Page:
www.facilities.calpoly.edu/sustainability/index.htm
- Biennial Sustainability Progress Report 2008
www.facilities.calpoly.edu/sustainability/SusInd08.pdf
- Capital Project News:
www.facilities.calpoly.edu/campusprojects/project_news.htm




QUESTIONS?

This concludes the American Institute of Architects Continuing Education Systems Program.

Please stop by the Higher Education Partnership booth for hard copies of 2007 Best Practice case studies.

Or visit

www.greenbuildings.berkeley.edu/best_practices.htm to view an online archive of case studies.



BEST PRACTICES

2008

